

RADC-TR-80-379, Vol III (of five) Final Technical Report

January 1981



AN ALGORITHMIC SOLUTION FOR A QUEUEING MODEL OF A COMPUTER SYSTEM WITH INTERACTIVE AND BATCH JOBS

Syracuse University

J. G. Shanthikumar Robert G. Sargent



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

FILE COPY

ROME AIR DEVELOPMENT CENTER Air Force Systems Command Griffiss Air Force Base, New York 13441

81 3 06 078

This report has been reviewed by the RADC Public Affairs Office (PA) and is releasable to the National Technical Information Service (NTIS). At NTIS it will be releasable to the general public, including foreign nations.

Volumes IV and V of this report will be published at a later date.

RADC-TR-80-379, Vol III (of five) has been reviewed and is approved for publication.

APPROVED:

CLEMENT D. FALZARANO Project Engineer

Clement & Thearans

APPROVED:

JOHN J. MARCINIAK, Colonel, USAF Chief, Information Sciences Division

FOR THE COMMANDER: John J. Kins

JOHN P. HUSS Acting Chief, Plans Office

If your address has changed or if you wish to be removed from the RADC mailing list, or if the addressee is no longer employed by your organization, please notify RADC.(ISIS) Griffiss AFB NY 13441. This will assist us in maintaining a current mailing list.

Do not return this copy. Retain or destroy.

MISSION of

Rome Air Development Center

RADC plans and executes research, development, test and selected acquisition programs in support of Command, Control Communications and Intelligence (C³I) activities. Technical and engineering support within areas of technical competence is provided to ESD Program Offices (POs) and other ESD elements. The principal technical mission areas are communications, electromagnetic guidance and control, surveillance of ground and aerospace objects, intelligence data collection and handling, information system technology, ionospheric propagation, solid state sciences, microwave physics and electronic reliability, maintainability and compatibility.

(19) MR-80-379-Vol-3)

UNCLASSIFIED

DEDOOT DOCHUSHTATION PAGE	READ INSTRUCTIONS
REPORT DOCUMENTATION PAGE	BEFORE COMPLETING FORM
RADC-TR-80-379, Vol III (of five) AD AO	76 043
AN ALGORITHMIC SOLUTION FOR A QUEUEING MODEL OF A COMPUTER SY TEM WITH INTERACTIVE AND BATCH JOBS.	Final Technical Report 1 Oct 77—30 Sep 80 6. PERFORMING 03G. REPORT SUMBER N/A
J. G. /Shanthikumar Robert G. /Sargent /	5 F30602-77-C-0235
Syracuse University School of Computer & Information Science Syracuse NY 13210	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62702F 625811903
Rome Air Development Center (ISIS) Griffiss AFB NY 13441	January 381
Same	
(7)35	15. DECLESSIFICATION/DOWNGRADING
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, If differently and statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement of the abstract entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20, If differently and a statement entered in Block 20,	nt (rom Report)
RADC Project Engineer: Clement D. Falzaran	o (ISIS)
19. KEY WORDS (Continue on reverse side if necessary and identity by block in Programming Systems; Programming Languages; Programs Correct; Computer Modeling; System ithm; Logic Programming.	Programming Grammars; Proving
Programming Systems; Programming Languages; Programs Correct; Computer Modeling; System	Programming Grammars; Proving Simulation; Scheduling Algorded into four project areas, a fectively, reliably and efficace of applications. of communicating with compute stems (P.I: J.A. Robinson). features developed to support

410 176

也可以是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们是一个人,我们

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

Item 20 (Cont'd)

。 1906年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1908年,1

program development into a new conceptual framework that can be understood and used by a large community of users.

- Task 2. Proving Program Correctness (P.I: J.C. Reynolds). This group is working towards programming language designs which increase the probability that specification errors will be detected by the compiler or interpreter and to provide the language facilities so that users will more nearly be able to prove that programs perform as they are specified than is currently possible.
- Task 3. Grammars of Programming (P.I: E.F. Storm). This group is working towards the development of methods which will allow users to communicate with computer programs in terms more normal to their every day communication forms.
- Task 4. Systems Studies (P.I: R.G. Sargent). This group is working towards developing more sophisticated and efficient models of computer systems which can predict system performance when given particular parameter values. The current efforts concern models of transaction processing systems (TPS).

UNCLASSIFIED

Helender Franklicher in der Steinbergerender in der Steinbergerende in der Stein


Preface

This report describes efforts completed in the Language Studies project at Syracuse University under RADC contract F30602-77-C-0235. The work covers the period October 1, 1977 through September 30, 1980.

The report is produced in five volumes to facilitate single volume distribution.

- Volume 1. Report from the Very High Level Programming Systems task. Report title is "Logic Programming in Lisp".
- Volume 2. Report from the Systems Studies task. Report title is "Multiple Finite Queueing Model with Fixed Priority Scheduling".
- Volume 3. Report from the Systems Studies task. Report title is "An Algorithmic Solution for a Queueing Model of a Computer System with Interactive and Batch Jobs.
- Volume 4. Report from the Grammars of Programming task. Report title is "Programming Control Structures in a High Level Language.
- Volume 5. Report from the Proving Program Correctness task.

 Report title is "Realignment".



AN ALGORITHMIC SOLUTION FOR A QUEUEING MODEL OF A
COMPUTER SYSTEM WITH INTERACTIVE AND BATCH JOBS

ABSTRACT

A queueing model with two customer classes, one with infinite and the other with finite source, is used as a model for a computer system with interactive and batch jobs. Using an imbedded Markov Chain representation of this queueing system, and an algorithmic approach, the steady state joint probability distribution of the number of interactive and batch jobs at a job service completion epoch is derived. Server utilization, mean waiting times, joint probability distribution, and mean number of interactive and batch jobs at an arbitrary time epoch are derived using these probabilities, discrete state level crossing analysis and Little's result.

Key Words: Computer Systems Modelling, Priority Queues, Imbedded Markov Chain, Algorithmic Solution, Level Crossing Analysis.

1. INTRODUCTION

The intent of this paper is to present an algorithmic solution for a queueing model of a computer system with interactive and batch jobs. Interactive jobs arrive from a finite number of interactive terminals and batch jobs arrive from an infinite size population.

Once an interactive job arrives to the computer system, the corresponding terminal stays passive until the job is processed, at which time the terminal becomes active and begins the process of submitting a new job.

The queueing models associated with this system are special cases of priority queues with two classes of customers with one finite and the other infinite sources. Models in which the finite source jobs having preemptive priority over infinite source jobs have been extensively analyzed by Avi-Itzhak and Naor [1], Colard and Latouche [2], Jaiswal [4], Jaiswal and Thiruvengadam [5], and Thiruvengadam [12]. While the technique used in [1, 4, 5, 12] is complex and obtaining numerical results is difficult, the algorithmic approach discussed by Colard and Latouche [2] is very efficient. This efficiency comes from the fact that the above model can be treated as a special case of an M/PH/1 queue. Simple explicit results for this M/PH/1 queue can be found in Neuts [10].

In this paper, however, we shall assume that the priority discipline is non-preemptive. So we shall model the computer system by a queueing system with two classes of customers and non-preemptive priority service discipline. Using an imbedded Markov chain representation of this queueing system and an algorithmic approach discussed by Lucantoni and Neuts [8] and Neuts [9], the steady state joint probability distribution of the number of interactive and batch jobs at a job service completion epoch is derived. Server utilization, mean waiting times, joint probability distribution and mean number of interactive and batch jobs at an arbitrary time epoch are derived using these probabilities, discrete state level crossing analysis [11], and Little's result [6].

2. THE MODEL

The model class considered here is of a single server queueing system to which the arrivals form two independent arrival streams, one from a finite and the other from an infinite population source. The time needed by each of the M members in the finite source, to submit a job (hereafter called interactive job) is exponential with mean $1/\lambda_1$. The jobs from the infinite source (hereafter called batch jobs) arrive to the server according to a Poisson process with rate λ_0 . The service requirements of these jobs at the server are general with probability distribution function $B_0(\cdot)$ for batch and $B_1(\cdot)$ for interactive jobs with means $1/\mu_0$ and $1/\mu_1$, respectively. The service discipline is non-preemptive priority. In this paper we consider two cases, one in which the interactive jobs have higher priority over the batch jobs and the other in which these priorities are reversed.

KONONELE ELEMENTE ELEMENTE ELEMENTO CONTROL ELEMENTO ELEM

It is routinely verified that the number of interactive and batch jobs just after a service completion, in this model, forms a Markov chain. Let {(i,j), i>0, M>j>0} represent the state space with i representing the number of batch and j representing the number of interactive jobs. The transition probability matrix (TPM) P, of this Merkov chain is of the form:

į	_								٦	
	Во	^B 1	^B 2	^B 3	^B 4	•	•	•		
	^A 0	A ₁	A ₂	A ₃	A ₄	•	•	•		
	0	^A 0	A ₁	A ₂	A ₃	•	•	•	• [
	0	0	A _O	A ₁	A ₂	•	•	•	.	
	0	0	0	A ₀	A ₁	•	•	•		
	0	0	0	0	A 0	•	•	•		
P =	0	0	0	0	0					
	•	•	•	•	•	•	•			
	•	•	•	•	•	•	•	•		
	•	•	•	•	•	•	•	•		
	•	•	•	•	•	•	•	•		
	•	•	•	•	•	•	٠	•		
	•	•	•	•	•	•	٠	•	•	
	L								أ	

where the matrices A_r , $r \ge 0$ and B_r , $r \ge 0$ are all square substochastic matrices of order M+1. The matrices

$$B = \sum_{r=0}^{\infty} E_r \qquad \text{and} \qquad A = \sum_{r=0}^{\infty} A_r$$

are both stochastic.

Let $A_r(i,j)$ and $B_r(i,j)$, i=0,1,2,...,M; j=0,1,2,...,M, be the (i+1,j+1)th entry of the A_r and B_r matrices, respectively. Then if $\chi(n)$ is the state of the Markov chain at the n-th transition,

$$A_{r}(i,j) = P\{X(n+1) = (k+r-1,j) | X(n) = (k,i)\}, k > 0$$

and

$$B_r(i,j) = P\{\chi(n+1) = (r,j) | \chi(n) = (0,i)\}$$

for all i,j = 0,1,2,...,M and n>0. The exact values of these entries will depend on λ_0 , λ_1 , $B_0(\cdot)$, $B_1(\cdot)$, and the priority assignment. Before discussing these entries any further, we will first outline the algorithmic approach used to analyze the Markov chain with the structure of P for the TPM. This approach, as a general methodology, was introduced by Lucantoni and Neuts [8] and Neuts [9]. In this section, however, we will present the necessary results only.

Let x_i be the steady state probability vector with the partion $x_i = (x_0, x_1, \ldots)$ where x_i , $i \ge 0$ are all (M+1)-vectors. These steady state probabilities are the solution to the set of equations,

$$\chi_{0}^{B_{0}} + \chi_{1}^{A_{0}} = \chi_{0}$$

$$\chi_{0}^{B_{k}} + \sum_{r=1}^{k+1} \chi_{r}^{A_{k+1-r}} = \chi_{k}, \quad k \ge 1$$
(1)

作品,这种种种,我们是是一种,我们是一种,我们是是一种,我们是是一种,我们也是一种,我们也是一种,我们也是一种,我们也是一种,我们是一种的,我们也是一种的,我们 第一种是一种是一种是一种是一种,我们是一种是一种,我们是一种是一种,我们也是一种是一种,我们也是一种是一种,我们也是一种是一种,我们也是一种的,我们就是一种的,

with the normalizing condition

where g = (1,1,...) is of appropriate dimension. Next we present the condition for the existence of a steady state solution. Assuming that the matrix A is irreducible, let χ be the solution to

$$\pi^{A} = \pi, \pi e = 1$$
 (2)

and β be given by

$$\beta = \sum_{r=1}^{\infty} r A_{r} e \qquad (3)$$

Then for stationarity (see Neuts [9]),

$$\rho = \pi \beta < 1 \quad . \tag{4}$$

If this condition is satisfied, the steady state joint probability distribution for this Markov chain is given by (see [8]),

$$\begin{array}{c}
\chi_0 = \frac{\ell}{\ell \cdot \ell^*} \\
\chi_1 = \frac{k}{k \cdot k^*}
\end{array}$$
(5)

where these quantities d, k, d*, and k* are defined in the appendix.

The other elements of the steady state probability vector are obtained using the iterative equations

where

$$b_k^* = (x_0 B_k + x_1 A_k) (I - A_1)^{-1}$$

and

$$A'_{r} = A_{r}(I-A_{1})^{-1}, r \ge 0$$
.

These iterations of $\chi_k(n)$ are continued until a sufficient accuracy is achieved for χ_k . The marginal probabilities are

$$\mathbf{x_i} = \mathbf{x_i} \mathbf{e} , i \ge 0$$
 (7)

and

$$y = \sum_{i=0}^{\infty} x_i$$

for batch and interactive jobs, respectively.

It can be shown that (see equation (40) of [8])

$$\chi = \chi(1) = \left[\chi_0 \sum_{r=1}^{\infty} {}^{B}_r - \chi_1^{A_r} \right] (I - A + n)^{-1} + (1 - \chi_0 e) \pi$$
 (8)

where $\chi(Z) = \sum_{r=1}^{\infty} \chi_r Z^r$ and Π is an (M+1)x(M+1) matrix with identical columns equal to π .

The first moment of the stationary distribution is

$$\chi^{(1)}(1) = \{-\chi(1)[I - \sum_{r=1}^{\infty} rA_r] + \chi_0 \sum_{r=1}^{\infty} B_r + \chi_0 \sum_{r=1}^{\infty} rB_r - \chi_1 A_0\}(I - A + \Pi)^{-1} + (\chi^{(1)}(1) e)\chi,$$
(9)

where $\chi(1)$ and Π are as defined in (8) and $\chi^{(1)}(1)$ e is defined in the appendix.

Next, using these results and the discrete state level crossing analysis [11], we will derive the steady state joint and marginal probability distributions at an arbitrary time epoch.

Let q be the steady state joint probability vector at an arbitrary time epoch. Here $q = (q_0, q_1, \ldots)$ and $q_i = (q_1, q_{11}, \ldots, q_{1M})$. Then, the rate of upcrossings from the compound state $\{(i, j), i \le m, j \le n\}$ is (see [11]),

$$\lambda_0 \sum_{j=0}^{n} q_{mj} + n\lambda_1 \sum_{i=0}^{m} q_{in}, \qquad (10)$$

since the arrivals are Markovian. Now let x^r_{ij} be the steady state probability that a type r (r=0 for batch and r=1 for interactive job) departing job sees i batch and j interactive jobs in the system. Then the rate of downcrossings into the compound state $\{(i,j), i \le m, j \le n\}$ is (see [11]),

$$\rho_0^{\mu_0} = \sum_{j=0}^{n} x_{mj}^0 + \rho_1^{\mu_1} = \sum_{i=0}^{m} x_{in}^1 , \qquad (11)$$

where ρ_i is the fraction of time the server is busy with type i jobs. Now equating the rates of up- and downcrossings, from (10) and (11) we get

$$\lambda_{0} \sum_{j=0}^{n} q_{mj} + n\lambda_{1} \sum_{i=0}^{m} q_{in} = \rho_{0} \mu_{0} \sum_{j=0}^{n} x_{mj}^{0} + \rho_{1} \mu_{1} \sum_{i=1}^{m} x_{in}^{1}.$$

Rearranging terms, we get a recursive formula for the unknowns $\boldsymbol{q}_{\boldsymbol{m}\boldsymbol{n}}.$ It is

$$q_{mn} = \frac{1}{\lambda_0 + n\lambda_1} \{\rho_0 \mu_0 x_{mn}^0 + \rho_1 \mu_1 x_{mn}^1 + \sum_{j=0}^{n-1} (\rho_0 \mu_0 x_{mj}^0 - \lambda_0 q_{mj}) + \sum_{j=0}^{m-1} (\rho_1 \mu_1 x_{in}^1 - n\lambda_1 q_{in}), 0 \le n \le M, m \ge 0$$
(12)

Next we derive the marginal probabilities associated at an arbitrary time epoch.

(1) Interactive Jobs

Equating the rates of up- and downcrossings (see page 21 of [11]), we get

$$n\lambda_1 q^1_n = \rho_1 \mu_1 x^1_n$$
, $0 \le n \le M$ (13)

where $x = \sum_{i=0}^{\infty} x^{i}$ and q^{i} is the steady state probability that there are n interactive jobs in the system at an arbitrary time epoch. Then

$$q_{n}^{1} = \frac{\rho_{1}\mu_{1}}{n\lambda_{1}} \quad x_{n}^{1}, \quad 0 \le n < M$$

$$q_{M}^{1} = 1 - \sum_{i=0}^{M-1} q_{i}^{1}$$
(14)

and

(ii) Batch Jobs

Using a similar derivation as above (see [11]), we get

$$\lambda_0 q_{\mathbf{m}}^0 = \rho_0 \mu_0 \mathbf{x}_{\mathbf{m}}^0 , \qquad (15)$$

where $x_m^0 = \sum_{j=0}^M \sum_{mj} x_{mj}^0$ and q_m^0 is the steady state probability that there are m batch jobs in the system at an arbitrary time epoch. Since all batch jobs are serviced, $\rho_0 \mu_0 = \lambda_0$. Substituting this in (15), we have

$$q_{m}^{0} = x_{m}^{0}, m \ge 0$$
 (16)

The following section provides equations to evaluate the mean number of jobs in the system at an arbitrary time epoch, and the mean waiting times.

(i) Interactive Jobs

Let the effective interactive job arrival rate be λ_e^1 . Then $\lambda_e^1 = \rho_1 \mu_1$. If L_1 is the mean number of interactive jobs at the server at an arbitrary time epoch, and W_1 is its mean waiting time,

$$\lambda_{e}^{1} = (M-L_{1})\lambda_{1}$$

or

$$L_1 = M - \rho_1 \mu_1 / \lambda_1 \tag{17}$$

Now from (17) and Little's result [6],

$$W_1 = (M/\rho_1 \mu_1) - 1/\lambda_1 . {18}$$

(ii) Batch Jobs

Let L_0 and N^0 be the mean number of batch jobs in the system at an arbitrary time epoch and just after a batch jobs service completion, and W_0 its mean waiting time. Then

$$L_0 = N^0 , \qquad (19)$$

since $q_{m}^{0} = x_{m}^{0}$, and from Little's result,

$$W_0 = L_0/\lambda_0 \tag{20}$$

To use (12), (14), (16)-(19), and (20), we need \mathbf{x}_{ij}^r , ρ_r , r = 0,1, and \mathbf{N}^0 . These can be related to \mathbf{x} and $\mathbf{X}^{(1)}(1)$ depending on the priority rule used. We shall derive these relationships later for each case, separately. The following definitions will be used in both cases.

 $P_i(n,r:k) = P\{n \text{ batch jobs and } r \text{ interactive jobs arrive during a time interval which has a probability distribution } B_i(\cdot), given there are k interactive jobs left in the source at the beginning of this time interval}.$

CASE 1: Interactive Jobs Have Higher Priority Over Batch Jobs

Here we assume that the interactive jobs have higher priority over batch jobs. That is, if there is at least one interactive job available at a service completion epoch, it will go in for service. Then the entries of the matrix \mathbf{A}_r are given by,

for r≥l

$$A_{r}(i,j) = \begin{cases} P_{1}(r-1,j+1-i:M-1) & M \ge i > 0; & M \ge j \ge i-1 \\ 0 & M \ge i > 0; & i-1 > j \ge 0 \\ P_{0}(r,j:M) & i=0; & M \ge j \ge 0 \end{cases}$$

and for r=0

$$A_0(i,j) = \begin{cases} 0 & \text{M>i>0; M>j>0} \\ P_0(0,j:M) & i=0; M>j>0 \end{cases}$$

Similarly, for $r \ge 0$

$$B_{\mathbf{r}}(i,j) = \begin{cases} A_{\mathbf{r}+1}(i,j) & \text{M>i>0; M>j>0} \\ a_{0}P_{0}(\mathbf{r},j:M) + a_{1}P_{1}(\mathbf{r},j:M-1) & \text{1=0:M-1>j>0} \\ a_{0}P_{0}(\mathbf{r},M:M) & \text{i=0; j=M} \end{cases}$$

where
$$a_0 = \frac{\lambda_0}{\lambda_0 + M\lambda_1}$$
 and $a_1 = \frac{M\lambda_1}{\lambda_0 + M\lambda_1}$. (21)

These probabilities can be evaluated in a recursive manner and the details are given in the appendix. Now to use equations (12), (14), (16)-(19), and (20), we need χ^0 , χ^1 , ρ_0 , ρ_1 , and N^0 . We will derive these next.

Since for an interactive job to leave behind i batch and n interactive jobs, an interactive job must go in for service, thus the use of conditional probability and convolution arguments lead to
$$x_{in}^{1} = \{ \sum_{k=1}^{i} \sum_{j=1}^{n+1} x_{kj}^{A} A_{i+1-k}(j,n) + \sum_{j=1}^{n+1} x_{0j}^{B} B_{i}(j,n) + a_{1}^{2} x_{00}^{B} B_{i}(0,n) \} / p_{1}$$
 (22)

and

$$x_{n}^{1} = \sum_{i=0}^{\infty} x_{in}^{1} , \qquad (23)$$

where p₁ is the probability that a departing job is interactive. Now for batch jobs,

$$x_{mj}^{0} = (\sum_{i=1}^{m+1} x_{i0}^{A_{m+1-i}}(0,j) + a_{0}^{2} x_{00}^{B_{m}}(0,j))/p_{0}, \qquad (24)$$

where $p^{\mathbb{C}}$ is the probability that a departing job is a batch job. Then

$$x^{0}_{m} = \sum_{j=0}^{M} x^{0}_{mj}$$

$$= \frac{1}{P_{0}} \left\{ \sum_{j=1}^{m+1} \sum_{j=0}^{M} \sum_{m+1-1}^{M} (0,j) + a_{0}x_{00} \sum_{j=0}^{M} \sum_{m}^{M} (0,j) \right\}.$$

After some simplification, and using the normalizing condition, we get

$$x_{m}^{0} = \{ \sum_{i=1}^{m+1} x_{i0}^{p(m+1-i)} + a_{0}^{x_{00}^{p(m)}} \}/p_{0}, \qquad (25a)$$

THE STATE OF THE PROPERTY OF T

where P(n) is the probability the n batch jobs arrive during the service of a batch job, and

$$p_0 = \sum_{i=1}^{\infty} x_{i0} + a_0 x_{00} . {(25b)}$$

Using the theory of Markov Renewal Processes (see J.J. Hunter [3]), it can be shown that

$$\rho_0 = (\sum_{i=1}^{\infty} x_{i0} + a_0 x_{00}) \frac{1}{\mu_0} / EC$$
,

where

$$EC = (\sum_{i=1}^{\infty} x_{i0} + a_0 x_{00}) \frac{1}{\mu_0} + (\sum_{i=0}^{\infty} \sum_{j=1}^{M} x_{ij} + a_1 x_{00}) \frac{1}{\mu_1} + \frac{x_{00}}{\lambda_0 + M \lambda_1}$$

and

$$\rho_1 = (\sum_{i=0}^{\infty} \sum_{j=1}^{M} x_{ij} + a_1 x_{00}) \frac{1}{\mu_1} / EC,$$

since ECxEN is the mean busy cycle time and $(\sum_{i=1}^{\infty} x_{i0} + a_0 x_{00}) \times EN/\mu_0$ and $(\sum_{i=1}^{\infty} x_{ij} + a_1 x_{00}) \times EN/\mu_1$ are the mean time in a busy cycle the server i=0 j=1 is busy with batch and interactive jobs, respectively, where EN is the mean number of jobs served during a busy cycle. Note that

$$\sum_{i=1}^{\infty} x_{i0} = y_0 - x_{00}$$

and

$$\sum_{i=0}^{\infty} \sum_{j=1}^{M} x_{ij} = 1 - y_0$$

and so from (25b)

$$p_0 = y_0 - x_{00} + a_0 x_{00}$$
 (25c)

是是一个人,我们是是一个人,我们是这个人,我们是我们的人,我们是这个人,我们是不是一个人,我们是不是一个人,我们是不是一个人,我们是这个人,我们是这个人,我们是这一个人

Next we evaluate N⁰. Since

$$N_0 = \sum_{\infty} m \times_0^m$$

from (25a) we get

$$N^{0} = \sum_{m=0}^{\infty} \prod_{i=1}^{m+1} x_{i0} P(m+1-i) + x_{00} a_{0} P(m) \}/p_{0}$$

$$= \{ \sum_{i=1}^{\infty} \sum_{m=i-1}^{\infty} x_{i0} P(m-(i-1)) + x_{00} a_{0} \sum_{m=0}^{\infty} P(m) \}/p_{0}$$

$$= \{ \sum_{i=1}^{\infty} ((i-1) + \sum_{i=0}^{\infty}) x_{i0} + x_{00} a_{0} p_{0} \}/p_{0}$$

$$= \{ \sum_{i=1}^{\infty} (1-p_{0}) (\sum_{i=1}^{\infty} x_{i0}) + a_{0} x_{00} p_{0} \}/p_{0}$$

$$= \{ x_{i}^{(1)} (1) (0) - (1-p_{0}) (y_{0} - x_{00}) + a_{0} x_{00} p_{0} \}/p_{0} \}$$

So

$$L_0 = \{\chi^{(1)}(1)(0) - (1-\rho_0)(y_0-x_{00}) + a_0x_{00}\rho_0\}/p_0$$
 (26)

and hence $W_0 = L_0/\lambda_0$ can be obtained once we evaluate χ . We can use (5) and (6) to obtain this provided A is irreducible and inequality (4) holds. From the definition of A_r , it is easily verified that the (i+1,j+1) the entry A(i,j) of A is given by

$$A(i,j) = \begin{cases} o^{\int_{-1}^{\infty} (\frac{M-i}{j+1-i})(1-e^{-\lambda_{1}t})^{j+1-i}e^{-(M-j-1)\lambda_{1}t} dB_{1}(t), & m \geq i > 0, \\ o^{\int_{-1}^{\infty} (\frac{M}{j})(1-e^{-\lambda_{1}t})^{j}e^{-(M-j)\lambda_{1}t} dB_{0}(t), & i = 0; \\ 0 & \text{Otherwise} \end{cases}$$

Similarly, β is given by

$$\mathcal{E} = (\lambda_0/\mu_0, \lambda_0/\mu_1, \lambda_0/\mu_1, \dots, \lambda_0/\mu_1)$$

Then the necessary and sufficient condition for the existance of χ is

$$\rho = \pi\beta < 1 ,$$

where

$$\pi A = \pi$$
.

CASE 2: Batch Jobs Have Higher Priority Over Interactive Jobs

In this section we assume that the batch jobs have higher priority over interactive jobs. That is, if there is at least one batch job available at a service completion epoch, it will go in for service. From the definition of $P_i(n,r:k)$ it is easily verified that, HINTER OF THE PROPERTY OF THE

for r≥0

$$A_{r}(i,j) = \begin{cases} P_{0}(r,j-i:M-i), M \ge i \ge 0; M \ge j \ge i \\ \\ 0 & M \ge i \ge 0; i > j \ge 0 \end{cases}$$

and

$$B_{r}(i,j) = \begin{cases} P_{1}(r,j+1-i:M-i) & M \geq i > 0; M \geq j \geq i-1 \\ a_{0}P_{0}(r,j:M) + e_{1}P_{1}(r,j:M-1), & i=0;M-1 \geq j \geq 0 \\ a_{0}P_{0}(r,M:M) & i=0; j=M \end{cases}$$

$$0 & \text{otherwise}$$

As indicated in the previous case, these probabilities can be evaluated recursively. Now we will derive expressions for $\rho_0, \rho_1, \chi^0, \chi^1$, and N^0 .

Similar to the previous case, using Markov Renewal Theory, we get

$$\rho_0 = (\sum_{m=1}^{\infty} (x_m) + a_0 x_{00}) \frac{1}{\mu_0} / EC$$

where

$$EC = (\sum_{j=1}^{M} x_{0j} + a_1 x_{0j}) \frac{1}{\mu_1} + (\sum_{m=1}^{\infty} (x_m) + a_0 x_{00}) \frac{1}{\mu_0} + \frac{x_{00}}{\lambda_0 + M\lambda_1}$$

and

$$\rho_1 = (\sum_{j=1}^{M} x_{0j} + a_1 x_{00}) \frac{1}{\mu_1} / EC$$
.

Note that
$$\sum_{m=1}^{\infty} (x_m) = 1 - x_0$$
 and $\sum_{j=1}^{M} x_{0j} = x_0 - x_{00}$.

The relationships for χ^0 and χ^1 with respect to χ is presented next. These results follow from simple convolution arguments and conditional probabilities.

$$x_{mj}^{0} = \{ \sum_{i=1}^{m+1} \sum_{k=0}^{j} x_{ik} p_{0}(m+1-i, j-k:M-k) + x_{00} a_{0} P_{0}(m,j:M) \} / p_{0} ,$$

where \mathbf{p}_0 is the probability that a departing job is . batch job, and so

$$x_{m}^{0} = \sum_{j=0}^{M} x_{mj}^{0}$$

$$x_{m}^{m+1} = \sum_{i=1}^{m+1} x_{i}^{2} P(m+1-i) + x_{00}^{a} P(m) \}/p_{0}, \qquad (27)$$

where $p_0 = 1 - x_0 + a_0 x_{00}$. Therefore

$$N^{0} = \sum_{m=0}^{\infty} m x^{0}_{m}$$

$$= \sum_{m=0}^{\infty} \sum_{i=1}^{\infty} \sum_{m=0}^{\infty} (i-1+\rho_{0})^{2} x_{i} + a_{0}x_{00}^{\rho_{0}} p^{\rho_{0}} p^{\rho_{0}$$

So

$$L_0 = \{ \chi^{(1)}(1) e - (1-\rho_0)(1-x_0) + a_0 x_{00} \rho_0 \} / \rho_0$$
 (28)

and $W_0 = L_0/\lambda_0$ can be obtained once χ is known.

Now for x^{1}_{in} we have from convolution arguments,

$$x^{1}_{in} = \{ \sum_{j=1}^{n+1} x_{0j} P_{1}(i,n+1-j:M-j) + a_{1}x_{00} P_{1}(i,n:M-1) \} / p_{1}, \qquad (29)$$

where p_1 is the probability that a departing job is interactive and

$$x^{1}_{n} = \sum_{i=0}^{\infty} x^{1}_{in}, \underline{M \ge n \ge 0}.$$
 (30)

Now we will specify the condition for the existence of x. Considering A, it is clear that A is an upper triangular matrix whose entries, with notation as defined in the previous case, are

$$A(i,j) = \begin{cases} o^{\int_{0}^{\infty} (M-i)^{2} (1-e^{-\lambda_{1}t})^{j-i} e^{-\lambda_{1}(M-j)t} dB_{0}(t), & M \ge i \ge 0; & M \ge j \ge i \\ 0 & \text{otherwise} \end{cases}$$

Clearly A is reducible and therefore the condition (4) cannot be directly used. However, using an analysis similar to that of Lucantoni [7] page 7, it can be established that the necessary and sufficient condition for stability is

$$\lambda_0/\mu_0 < 1 .$$

3. NUMERICAL RESULTS

The algorithm generating these performance measures was implemented in APL. Some sample results for different input parameters λ_0 , λ_1 , μ_0 , μ_1 , and M for exponential service times are shown in Tables 1 and 2.

	Mean number of jobs in the system at an arbitrary time epoch when higher priority is given to					
Batch Jobs Arrival	Inter	active Jobs	Batch Jobs			
Rate λ_0	Batch	Interactive	Batch	Interactive		
.05	0.2835	0.5875	0.2567	0.6841		
.075	0.5133	0.7376	0.4394	0.9565		
.10	0.8569	0.8878	0.6821	1.2890		
.125	1.4190	1.0380	1.0210	1.6920		
.15	2.4879	1.1881	1.5265	2.1713		
.175	5.2676	1.3383	2.3663	2.7365		

Batch jobs service rate μ_0 = 0.25 Number of Interactive terminals N = 5 Interactive job arrival rate λ_1 = 0.1 Interactive jobs service rate μ_1 = 2.0

TABLE 1

TABLE 2

4. CONCLUSION

In this paper we have modelled the computer system with batch and interactive jobs as a single server queueing system with two classes of customers and non-preemptive priority service discipline. The system performance measures were numerically evaluated using an algorithmic approach proposed by Neuts [9] and a discrete state level crossing analysis (see [11]).

APPENDIX

(a) Recursive Evaluation of Transition Probabilities

Define

 $P_i(n,r:k) = P\{n \text{ batch jobs and } r \text{ interactive jobs arrive during}$ a time interval which has probability distribution $B_i(\cdot)$ given there are k interactive jobs left in
the source at the beginning of this time interval}.

That is

$$P_{i}(n,r:k) = o^{\int_{0}^{\infty} \frac{e^{-\lambda_{0}t}(\lambda_{0}t)^{n}}{n!}} {\binom{k}{r}(1-e^{-\lambda_{1}t})^{r}} e^{-(k-r)\lambda_{1}t} dB_{i}(t), i=0,1$$

$$= \frac{\lambda_{0}^{n}}{n!} {\binom{k}{r}}_{o} \int_{0}^{\infty} e^{-\lambda_{0}t} t^{n} {\binom{r}{r}}_{j=0} {\binom{r}{j}} {(-1)^{j}} e^{-j\lambda_{1}t} e^{-(k-r)\lambda_{1}t} dB_{i}(t)$$

$$= \frac{\lambda_{0}^{n}}{n!} {\binom{k}{r}}_{j=0}^{r} {(-1)^{j}}_{j=0}^{r} {\binom{r}{j}}_{o} \int_{0}^{\infty} t^{n} e^{-(\lambda_{0}+(k+j-r)\lambda_{1}t)} dB_{i}(t)$$

$$= \frac{\lambda_{0}^{n}}{n!} {\binom{k}{r}}_{j=0}^{r} {(-1)^{j}}_{j=0}^{r} {\binom{r}{j}}_{o} \int_{0}^{\infty} t^{n} e^{-(\lambda_{0}+(k+j-r)\lambda_{1}t)} dB_{i}(t)$$

=
$$(-1)^n \frac{\lambda_0^n}{n!} {k \choose r}_{j=0}^r (-1)^j {r \choose j} B_i^{(n)} (\lambda_0 + (k+j-r)\lambda_1)$$
,

where

$$\hat{\mathbf{B}}_{\mathbf{i}}^{(n)}(\mathbf{a}) = \lim_{\mathbf{s} \to \mathbf{a}} \frac{\mathbf{d}^n}{\mathbf{d}\mathbf{s}^n} \hat{\mathbf{B}}_{\mathbf{i}}(\mathbf{s})$$

and

$$B_{i}(s) = o^{j^{\infty}} e^{-sx} dB_{i}(x) , i=0,1 .$$

Now consider

$$P_{i}^{(n,r:k+1)} = (-1)^{n} \frac{\lambda_{0}^{n}}{n!} {k+1 \choose r} \sum_{j=0}^{r} (-1)^{j} {r \choose j} \tilde{B}_{i}^{(n)} (\lambda_{0}^{+(k+1+j-r)\lambda_{1}}) .$$

Using the substitution

$$\binom{r}{j} = \binom{r-1}{j} + \binom{r-1}{j-1}$$

we get, after some manipulation,

$$P_{\mathbf{i}}(n,r:k+1) = (-1)^{n} \frac{\lambda_{0}^{n}}{n!} {k+1 \choose r} \sum_{j=0}^{r-1} (-1)^{j} {r-1 \choose j} \hat{B}_{\mathbf{i}}^{(n)} (\lambda_{0} + (k+j-(r-1)\lambda_{1}))$$

$$- (-1)^{n} \frac{\lambda_{0}^{n}}{n!} {k+1 \choose r} \sum_{j=0}^{r-1} (-1)^{j} {r-1 \choose j} \hat{B}_{\mathbf{i}}^{(n)} (\lambda_{0} + (k+1+j-(r-1)\lambda_{1}))$$

=
$$\{\binom{k+1}{r}/\binom{k}{r-1}\}\dot{P}_{i}(n,r-1:k) - \{\binom{k+1}{r}/\binom{k+1}{r-1}\}\dot{P}_{i}(n,r-1:k+1)$$

That is,

$$P_{i}(n,r:k+1) = (\frac{k+1}{r})P_{i}(n,r-1:k) - (\frac{k+2-r}{r})P_{i}(n,r-1:k+1) ,$$

$$n \ge 0; r \le k \le M$$
(A2)

Note that

$$P_{i}(n,r:k+1) = 0$$
 for all r>k+1

and

$$P_{\mathbf{i}}(n,0:k) = (-1)^{n} \frac{\lambda_{0}^{n}}{n!} \hat{B}_{\mathbf{i}}^{(n)}(\lambda_{0}+k\lambda_{1}), \, \underline{M \geq k \geq 0}.$$

Then using (A2), $P_i(n,r:k)$ can be calculated in a recursive fashion. That is, for r=1, calculate $P_i(n,1:k)$, k = 1,2,...,M, using (A2) and then r=2, etc.

(b) Quantities Needed in the Analysis of the Imbedded Markov Chain (taken from Lucantoni and Neuts [8]).

$$A^{\star}(Z) = \sum_{r=0}^{\infty} Z^{r} A_{r}$$

$$\chi(z) = \sum_{r=1}^{\infty} z^r \chi_r$$

$$G(Z) = \sum_{r=0}^{\infty} ZA_r G^r(Z) = ZA^*(G(Z))$$

$$G = \sum_{r=0}^{\infty} A_r G^r$$

$$\beta = \sum_{r=1}^{\infty} rA_r e$$

$$\xi^G = \xi$$
 , $\xi \xi = 1$

 \mathcal{G} is a square matrix with all row vectors identical to \mathcal{G} .

 $\Delta(\beta)$ is a diagonal matrix of order M+1 with diagonal entries β_0 , β_1 , ..., β_M .

$$H(Z) = Z[I - \sum_{r=1}^{\infty} ZA_r G^{r-1}(A)]^{-1}A_0$$

$$L(Z) \approx ZB_{r} + \sum_{r=1}^{\infty} ZB_{r}G^{r-1}(Z)H(Z)$$

$$K(Z) = ZA_0(I-ZB_0)^{-1} \sum_{r=1}^{\infty} ZB_rG^{r-1}(Z) + \sum_{r=1}^{\infty} ZA_rG^{r-1}(Z)$$

TOTAL STATES STATES STATES AND STATES STATES

$$dL(1) = d$$
 and $de = 1$

$$kK(1) = k$$
 and $ke = 1$

$$d^* = L^1(1)g$$

$$h^* = H^1(1)e$$

$$k^* = k^1(1)g$$

$$h^* = (I - \sum_{r=1}^{\infty} A_r G^{r-1})^{-1} \{ e + [\sum_{r=1}^{\infty} A_r - \sum_{r=1}^{\infty} A_r G^{r-1} + \sum_{r=2}^{\infty} (r-1) A_r \tilde{G}] (I - G + \tilde{G})^{-1} \mu \},$$

$$d^* = e + \sum_{r=1}^{\infty} B_r G^{r-1} h^* + \left[\sum_{r=1}^{\infty} B_r - \sum_{r=1}^{\infty} B_r G^{r-1} + \sum_{r=2}^{\infty} (r-1) B_r \tilde{G} \right] (1-G+\tilde{G})^{-1} \mu$$

$$k^* = e + A_0 (I - B_0)^{-1} e + \{A_0 (I - B_0)^{-1} \begin{bmatrix} \sum_{r=1}^{\infty} B_r - \sum_{r=1}^{\infty} B_r G^{r-1} \\ r = 1 \end{bmatrix} + \sum_{r=2}^{\infty} (r-1) B_r G^{r-1} + \sum_{r=1}^{\infty} A_r - \sum_{r=1}^{\infty} A_r G^{r-1} + \sum_{r=2}^{\infty} (r-1) A_r G^{r-1} G^{r-1} G^{r-1} G^{r-1} + \sum_{r=2}^{\infty} (r-1) A_r G^{r-1} G^{r-$$

$$A_{n}^{*}(Z) = \frac{d^{n}}{dZ^{n}} A^{*}(Z)$$

$$\delta^{(0)}(1) = 1$$
, $\chi^{(0)}(1) = e$, $\chi^{(0)}(1) = \pi$, $\delta^{(1)} = \pi A_1^*(1)e$

$$\mu^{(1)}(1) = (I-A+II)^{-1} \beta - \delta^{(1)} \beta$$

$$\chi^{(1)}(1) = \pi^{A_1^*(1)(I-A+\Pi)^{-1}} - \delta^{(1)}\pi$$

for $n \ge 2$

$$\delta^{(n)}(1) = \sum_{r=1}^{n} {n \choose r} \pi A_r^*(1) \mu^{(n-r)}(1) - \sum_{r=1}^{n-1} \pi \mu^{(n-r)}(1) \delta^{(r)}(1)$$

$$\mu^{(n)}(1) = (I-A+II)^{-1} \sum_{r=1}^{n} {n \choose r} [A_r^*(1)-\delta^{(r)}(1)1] \mu^{(n-r)}(1)$$

$$- \left[\sum_{r=1}^{n-1} {n \choose r} \chi^{(r)}(1) \mu^{(n-r)}(1) \right] e$$

$$\chi^{n}(1) = \sum_{r=0}^{n-1} {n \choose r} \chi^{(r)}(1) \left[A_{n-r}^{*}(1) - \delta^{(n-r)}(1) I \right] (I-A+II)^{-1}$$

$$\begin{split} \chi^{(1)}(1) & \ell = \frac{1}{2(1-\rho)} \{ 2 \chi_0 \sum_{k=1}^{\infty} k B_k \ell + 2 \chi_0 \sum_{k=1}^{\infty} B_k \mu^{(1)}(1) + \chi_0 \sum_{k=2}^{\infty} k (k-1) B_k \ell \\ & + 2 \chi_0 \sum_{k=1}^{\infty} k B_k \mu^{(1)}(1) + \chi_0 \sum_{k=1}^{\infty} B_k \mu^{(2)}(1) - 2 \chi_1 A_0 \mu^{(1)}(1) \\ & - \chi_1 A_0 \mu^{(2)}(1) + \chi(1) \ell^{\delta^{(2)}(1)} \} - \chi(1) \mu^{(1)}(1). \end{split}$$

The evaluation G is carried out using the recursion (see page 6 of [8]).

$$\hat{G}(0) = (I-A_1)^{-1}A_0,$$

$$\hat{G}(k+1) = \sum_{v=0}^{\infty} (I-A_1)^{-1}A_vG^r(k), \text{ for } k>0$$

$$v\neq 1$$

REFERENCES

- [1] Avi-Itzhak, B. and P. Naor, "On a Problem of Preemptive Priority Queueing," Operations Research, 9 (1961), pp. 664-672.
- [2] Colard, J.P. and G. Latouche, "Algorithmic Analysis of a Markovian Model for a System with Batch and Interactive Jobs," Technical Report #52B, Applied Mathematics Institute, Univ. of Delaware, Newark, (1980).
- [3] Hunter, J.J., "On the Moments of Markov Renewal Processes," Adv. Appl. Prob., 1 (1969), pp. 188-210.
- [4] Jaiswal, N.K., Priority Queues, Academic Press, New York (1968).
- [5] Jaiswal, N.K. and K. Thiruvengadam, "Finite-Source Priority Queues," SIAM J. Appl. Math., 15 (1967), pp. 1278-1293.

が大力を行うには、大力を行うに対しているというできない。 では、大力を行うには、大力を行うに対しているというできない。 できないというできない。

- [6] Little, J.D.C., "A Proof of the Queueing Formula L = λW," Operations Research, 9 (1961), pp. 383-387.
- [7] Lucantoni, D.M., "A GI/M/c Queue With a Different Service Rate for Customers Who Need Not Wait An Algorithmic Solution," Technical Report #480, Applied Mathematics Institute, Univ. of Delaware, Newark (1979).
- [8] Lucantoni, D.M. and M.F. Neuts, "Numerical Methods for a Class of Markov Chains Arising in Queueing Theory," Technical Report #78/10, Dept. of Statistics and Computer Science, Univ. of Delaware, Newark (1978).
- [9] Neuts, M.F., "Queues Solvable Without Rouche's Theorem," Operations Research, 27 (1979), pp. 767-781.
- [10] Neuts, M.F., "Explicit Steady-State Solutions to Some Elementary Queueing Models," Technical Report #53.B, Applied Mathematics Institute, Univ. of Delaware, Newark (1980).
- [11] Shanthikumar, J.G. and M. Jeya Chandra, "Application of Level Crossing Analysis to Discrete State Processes in Queueing Systems," WP #80-010, Dept. of Industrial Engineering and Operations Research, Syracuse Univ., Syracuse (1980).
- [12] Thiruvengadam, K., "A Priority Assignment in Machine Interference Problem," Opsearch, 1 (1964), pp. 197-216.